



EDWARDIAN DRAGFACED

BUTTERLEY
BRICK

EDWARDIAN DRAGFACED



Manufactured to BS EN 771-1

Brick type

Category II, U, Clay Masonry Unit

Standard work size

215 x 102.5 x 65mm

Dimensional tolerances

Tolerance category: T2

Range category: R1

Compressive strength*

Group 1: $\geq 30\text{N/mm}^2$

Group 2: $\geq 25\text{N/mm}^2$

Water absorption

$\leq 15\%$

Durability

F2

Active soluble salts content

S2

Configuration*

Vertically Perforated

Group 1: 15-25% voids

Group 2: 25-35% voids

Dry weight per brick*

Group 1: 2.05kg

Group 2: 1.95kg

Pack size

495

Factory

Kirton

SKU

SKIRAYM1600VO

Sales +44 (0) 330 1231017

Technical +44 (0) 330 1231018

Email bricks@forterra.co.uk

*Group 1 and Group 2 bricks manufactured in Kirton can be identified by the batch numbers. Contact us for more information.

Disclaimer: The reproduction of colours and textures is only as accurate as the printing process will allow. Photographic samples should be used when shortlisting products but we advise that an actual sample should be seen before ordering.

Version 2

(Last published: 19/03/26)

Valid at the time of publication. Please check our website (www.forterra.co.uk) for the latest product information and documentation. For previous versions please contact us.

BES 6001

Responsible Sourcing

www.greenbooklive.com



BUTTERLEY



forterra.co.uk